



## Automatic Water Boiler

EB3FX, EB4FX, EB6FX, EB6TFX

- Built-in water filtration system
- Large, colour touchscreen display
- Narrow 250mm footprint
- Eco setting reduces volume of boiling water by 50%
- Intelligent predictive eco setting learns usage patterns and adjusts the water volume
- 7 day timer
- Adjustable water temperature – from 70°C – 98°C
- Enhanced diagnostics
- Easy descale, just follow the onscreen instructions. No tools required.



### Water Boiler Features

- High quality filtered boiling water on tap 24 hours a day
- Precise electronic temperature control system
- Large, colour touchscreen display.
- Narrow 250mm width
- Energy saving eco mode
- Energy saving Intelligent predictive eco mode
- 7-day programmable timer to conserve energy
- Insulated tank for minimal heat loss and energy conservation
- Built-in water filtration system improves water quality and reduces scale build-up
- High volume, easy change FilterFlow cartridge - removes sediment and impurities such as chlorine and reduces limescale build-up
- Adjustable water temperature - from 70°C - 98°C
- Screw cap and indicator probe to monitor limescale build up.
- Descaling process with step-by-step instructions provided on screen, so there is no need for an engineer
- Enhanced multi-level diagnostics
- Designed for connection to a potable cold water supply
- Water and power supplies can be fed from the underside so no wires or pipes are visible
- WRAS approved

### Cleaning and Servicing

- Easy clean stainless steel external finish and smooth black trim
- Easy clean removable drip tray
- Easy change filter cartridge
- Screw cap and indicator probe to monitor limescale build up.
- Easy descale process, there is no need for an engineer
- Enhanced diagnostics, the on screen diagnostic information will enable the engineer to identify the parts needed and repair your water boiler at first visit

### Overall Construction

- Long life incoloy element
- Mirror finish stainless steel
- Smooth ABS/PC trim
- Stainless steel water tank
- 1.8 metre cable and a 13 amp moulded plug on EB3FX
- Connection block for hard wiring EB4FX, EB6FX, EB6TFX

### Inclusive Accessories

- Removable drip tray
- Water feed hose (1m)
- FC04 5,600 litre filter cartridge

### Available Options

- EB3FX/PB Push button model
- EB3FX/TT Twin temperature model

### Available Accessories

- BR55 Wall mounting kit for EB3FX and EB4FX models
- BR56 Wall mounting kit for EB6FX and EB6TFX models
- FC04 5,600 litre filter cartridge
- DP10 Descaler powder



## Technical Data

	EB3FX	EB4FX	EB6FX	EB6TFX
Width (mm)	250	250	250	250
Depth (mm)	525	525	525	525
Height (mm)	600	600	690	690
Height from tap to drip tray (mm)	250	250	250	250
Depth excluding drip tray	470	470	470	470
Number of taps	1	1	1	2
Output per hour (litres)	31	45	60	60
Rapid Draw-off (litres)	11	11	18	18
Heat up time to working temperature (full tank capacity)	31	22	22	22
Recovery per minute (litres)	0.52	0.75	1	1
Water inlet connection (BSP male)	3/4"	3/4"	3/4"	3/4"
Water inlet pressure (bar)	6	6	6	6
Total power rating (kW)	3	4.5	6	6
Standby power consumption (kW)	0.1	0.1	0.1	0.1
Electrical supply 1N~+E 230V 50-60Hz Current Rating (Amps)	13	20	26	26
Net weight empty (kg)	13	13	16	16
Net weight full (kg)	28	28	38	38
Packed weight (kg)	15	15	18	18
Shipping volume (m3)	0.152	0.152	0.171	0.171
IPX Protection	IPX3	IPX3	IPX3	IPX3

